



PRODUCT FEATURES:

- Surface mounted
 - 20mm x 20mm welded satin finish stainless steel frame with welded corners and theft-resistant mounting
 - Wall hanger of 18 gauge steel
 - Solid web backing
 - Mirror glass complies to AS 1288:2021 Australian safety glass standards
 - Custom sizing available
- Overall Dimensions:
600mm W x 1800mm H

1.2mm Thick Frame: Model 782-2424 600mm x 600mm
Model 782-1830 450mm x 750mm
Model 782-1824 450mm x 600mm
Model 782-1624 400mm x 600mm
1.5mm Thick Frame: Model 782-2472 600mm x 1800mm*
Model 782-2460 600mm x 1500mm*
Model 782-2448 600mm x 1200mm*
Model 782-2440 600mm x 1000mm*
Model 782-2438 600mm x 950mm
Model 782-2430 600mm x 750mm
Model 782-2040 500mm x 1000mm*
Model 782-1872 450mm x 1800mm*
Model 782-1860 450mm x 1500mm*
Model 782-1840 450mm x 1000mm*
Model 782-1838 450mm x 950mm
Model 782-1836 450mm x 900mm
* These mirrors comply to AS 1428.1

PRODUCT DATA:

CONSTRUCTION:

MIRROR: Fabricated of first quality 6.35mm glass, triple silver-plated layer and thermosetting infrared cured paint backing with Poly-Glaze protective finish. All edges protected by shock-absorbing, neoprene tubing. Conforms to AS 1288:2021 Australian safety glass standards. **FRAME:** Fabricated of heavy gauge, one piece, roll formed stainless steel, 20mm x 20mm angle with corners heliarc welded, ground and polished smooth to a satin finish. Double strength continuous integral stiffener on all sides for added strength. Bevel on front of angle secures frame flush against mirror. **BACK:** Fabricated of galvanized steel, secured to frame with concealed screws, equipped with integral horizontal hanging brackets.

WALL HANGER: Fabricated of 18 gauge cold rolled steel, all welded construction to form rigid template.



INSTALLATION:



Secure concealed mounting bracket to wall with screws (not included) at holes provided.

NOTE: Provide in-wall backing at mounting screw locations. Secure concealed wall hanger 'I' bracket to wall with screws (not included). Position mirror over mounting bracket to engage hanger tabs. Slide mirror down and lock into position. Tighten with grab screws supplied.



GUIDE SPECIFICATION:

Mirror shall be framed with heavy gauge, one piece, roll formed 20mm x 20mm stainless steel angle with double strength continuous integral stiffener. Welded corners shall be polished to a uniform satin finish. Mirror shall be of first quality 6.35mm glass and protected by a shock absorbing, neoprene tubing with Poly-Glaze protective finish. Back of unit shall be galvanized steel secured to frame with concealed screws, equipped with integral horizontal hanging brackets and separate wall hanger for concealed mounting.





Half Mirror Width



Bradley

DWG NO. 782-2472

APPROVED BY:

Proudly customised design please approve SCALE: 1:20